



RIG #2

OPERATIONS BASE: LLOYDMINSTER

Carrier	BOP Equipment
Mainland M-40 4010 Engine Cat 3406 Rated HP 325 Transmission Allison 5860 Main Drum Brakes 25.4 cm X 101.6 cm Sandline Brakes 25.4 cm X 101.6 cm Drill Line 25.4 mm Sandline 14.28 mm X 2500 m	WSI Duke 152 mm Double Gate 21 Mpa Rated Tapped Top 2000 / 3000 Kill Spool C/W 50.8 mm Outlet and Valve 21 Mpa Rated Drilled for 2000 / 3000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up
Mast	Mobile Doghouse
Bw Rig 70-140,000 21.3 m Height Max Static Hookload 62,700 daN (4 lines) Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Blocks 75 Ton McKissick Lighting Incandescent and Quartz	2.95m X 4.57m Change House 2.95m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System
Handling Equipment	Safety Equipment
Foster 58-93 Tongs c/w Air Back-up BJ Mach 4 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment	4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Detector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines

Optional Pump and Tank



RIG #5

OPERATIONS BASE: LLOYDMINSTER

Carrier	BOP Equipment
Skytop RR 400 Drawworks 4210 Engine Cat C-10 Rated HP 365 Transmission Allison 750 Main Drum Brakes 25.4 cm X 106.6 cm Sandline Brakes 20.3 cm X 96.5 cm Drill Line 25.4 mm Sandline 14.28 mm X 3500 m Integrated control panel for X-Celerator	Townsend 152 mm Double Gate 35 Mpa Rated Tapped Top 2000 / 5000 Kill Spool C/W 50.8 mm Outlet and Valve 35 Mpa Rated Tapped and Bored for 2000 / 5000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up
Mast	Mobile Doghouse
Care Industries 72FS-150,000 21.95 m Height Max Static Hookload 66,700 daN (4 lines) Max Wind Capacity 129 kph Full Setback Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Blocks 75 Ton McKissick Lighting Incandescent and Quartz Integrated X-Celerator unit X-300	2.95m X 4.57m Change House 2.95m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System
Handling Equipment	Safety Equipment
Gill 58-93 Tongs c/w Air Back-up Gill Model 300 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment	4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Detector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines

Optional Pump and Tank



RIG #9

OPERATIONS BASE: LLOYDMINSTER

Carrier	BOP Equipment
Skytop RR 400 Drawworks 4210 Engine Cat C-10 Rated HP 365 Transmission Allison 750 Main Drum Brakes 25.4 cm X 106.6 cm Sandline Brakes 20.3 cm X 96.5 cm Drill Line 25.4 mm Sandline 14.28 mm X 3500 m Integrated control panel for X-Celerator	Townsend 152 mm Double Gate 35 Mpa Rated Tapped Top 2000 / 5000 Kill Spool C/W 50.8 mm Outlet and Valve 35 Mpa Rated Tapped and Bored for 2000 / 5000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up
Mast	Mobile Doghouse
Care Industries 72FS-150,000 21.95 m Height Max Static Hookload 66,700 daN (4 lines) Max Wind Capacity 129 kph Full Setback Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Blocks 75 Ton McKissick Lighting Incandescent and Quartz Integrated X-Celerator unit X-300	2.95m X 4.57m Change House 2.95m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System
Handling Equipment	Safety Equipment
Gill 58-93 tongs c/w air back-up Gill Model 300 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment	4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Eetector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines

Optional Pump and Tank



RIG #10

OPERATIONS BASE: LLOYDMINSTER

Carrier	BOP Equipment
Skytop RR 400 Drawworks 4210 Engine Cat C-10 Rated HP 365 Transmission Allison 750 Main Drum Brakes 25.4 cm X 106.6 cm Sandline Brakes 20.3 cm X 96.5 cm Drill Line 25.4 mm Sandline 14.28 mm X 3500 m	Townsend 152 mm Double Gate 35 Mpa Rated Tapped Top 2000 / 5000 Kill Spool C/W 50.8 mm Outlet and Valve 35 Mpa Rated Tapped and Bored for 2000 / 5000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up

Mast	Mobile Pump Tank
Care Industries 72FS-150,000 21.95 m Height Max Static Hookload 66,700 daN (4 lines) Max Wind Capacity 129 kph Full Setback Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Blocks 75 Ton McKissick Lighting Incandescent and Quartz	2005 Freightliner Engine Cat C-7 Rated HP 300 Automatic Transmission Allison 3000 RDS Gardner Denver TEE 4 X 5 21 Mpa Rated Seven Valve Manifold 35 Mpa Rated 4 X 3 Mission Charge Pump

Handling Equipment	Mudtank
Gill 58-93 Tongs c/w Air Back-up Gill Model 300 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment	Two Compartment 32 m3 Capacity 50.8 mm Mud Roll and Degasser Volume Gauge Indicator on Front Man Rated Davit Arm 50.8 mm Line Pipe Rated 35 Mpa

Safety Equipment	Mobile Doghouse
4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Eetector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines	2.95m X 4.57m Change House 2.95m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System



RIG #12

OPERATIONS BASE: LLOYDMINSTER

<p style="text-align: center;">Carrier</p> <p>Skytop RR 400 Drawworks 4210 Engine Cat C-10 Rated HP 365 Transmission Allison 750 Main Drum Brakes 25.4 cm X 106.6 cm Sandline Brakes 20.3 cm X 96.5 cm Drill Line 25.4 mm Sandline 14.28 mm X 3500 m</p>	<p style="text-align: center;">BOP Equipment</p> <p>Townsend 152 mm Double Gate 35 Mpa Rated Tapped Top 2000 / 5000 Kill Spool C/W 50.8 mm Outlet and Valve 35 Mpa Rated Tapped and Bored for 2000 / 5000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up</p>
<p style="text-align: center;">Mast</p> <p>Care Industries 72FS-150,000 21.95 m Height Max Static Hookload 66,700 daN (4 lines) Max Wind Capacity 129 kph Full Setback Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Blocks 75 Ton McKissick Lighting Incandescent and Quartz</p>	<p style="text-align: center;">Mobile Pump Tank</p> <p>2005 Freightliner Engine Cat C-7 Rated HP 300 Automatic Transmission Allison 3000 RDS Gardner Denver TEE 4 X 5 21 Mpa Rated Seven Valve Manifold 35 Mpa Rated 4 X 3 Mission Charge Pump</p>
<p style="text-align: center;">Handling Equipment</p> <p>Gill 58-93 Tongs c/w Air Back-up Gill Model 300 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment</p>	<p style="text-align: center;">Mudtank</p> <p>Two Compartment 32 m3 Capacity 50.8 mm Mud Roll and Degasser Volume Gauge Indicator on Front Man Rated Davit Arm 50.8 mm Line Pipe Rated 35 Mpa</p>
<p style="text-align: center;">Safety Equipment</p> <p>4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Detector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines</p>	<p style="text-align: center;">Mobile Doghouse</p> <p>2.95m X 4.57m Change House 2.95m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System</p>



RIG #17

OPERATIONS BASE: LLOYDMINSTER

Carrier	BOP Equipment
CIL 150 Drawworks 4210 Engine Cat C-II Rated HP 385 Transmission Allison 750 Main Drum Brakes 25.4 cm X 106.6 cm Sandline Brakes 20.3 cm X 96.5 cm Drill Line 25.4 mm Sandline 14.28 mm X 3500 m	Townsend 152 mm Double Gate 35 Mpa Rated Tapped Top 2000 / 5000 Kill Spool C/W 50.8 mm Outlet and Valve 35 Mpa Rated Tapped and Bored for 2000 / 5000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up
Mast	Mobile Doghouse
Care Industries 72FS-150,000 21.95 m Height Max Static Hookload 66,700 daN (4 lines) Max Wind Capacity 129 kph Full Setback Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Blocks 75 Ton McKissick Lighting Incandescent and Quartz	2.95m X 4.57m Change House 2.95m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System
Handling Equipment	Safety Equipment
Gill 58-93 Tongs c/w Air Back-up Gill Model 300 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment	4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Detector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines

Optional Pump and Tank



RIG #18

OPERATIONS BASE: LLOYDMINSTER

Carrier	BOP Equipment
CIL 150 Drawworks 4210 Engine Cat C-II Rated HP 385 Transmission Allison 750 Main Drum Brakes 25.4 cm X 106.6 cm Sandline Brakes 20.3 cm X 96.5 cm Drill Line 25.4 mm Sandline 14.28 mm X 3500 m	Townsend 152 mm Double Gate 35 Mpa Rated Tapped Top 2000 / 5000 Kill Spool C/W 50.8 mm Outlet and Valve 35 Mpa Rated Tapped and Bored for 2000 / 5000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up
Mast	Mobile Doghouse
Care Industries 72FS-150,000 21.95 m Height Max Static Hookload 66,700 daN (4 lines) Max Wind Capacity 129 kph Full Setback Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Blocks 75 Ton McKissick Lighting Incandescent and Quartz	2.95m X 4.57m Change House 2.95m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System
Handling Equipment	Safety Equipment
Gill 58-93 Tongs c/w Air Back-up Gill Model 300 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment	4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Detector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines

Optional Pump and Tank



RIG #26

OPERATIONS BASE: LLOYDMINSTER

Carrier	BOP Equipment
CBI Drawworks 4210 Engine Cat C-II Rated HP 385 Transmission Allison OFS 4700 Main Drum Brakes 25.4 cm X 106.6 cm Sandline Brakes 20.3 cm X 96.5 cm Drill Line 25.4 mm Sandline 14.28 mm X 2400 m Integrated control panel for X-Celerator	IEI 152 mm Double Gate 35 Mpa Rated Tapped Top 2000 / 5000 Kill Spool C/W 50.8 mm Outlet and Valve 35 Mpa Rated Tapped and Bored for 2000 / 5000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up

Mast	Mobile Doghouse
Courtney Berg 72FS -125,000 21.95 m Height Max Static Hookload 56,000 daN (4 lines) Max Wind Capacity 129 kph Full Setback Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Rod X-Celerator - X-300 Rated 16,000 lbs Blocks 75 Ton McKissick Lighting Incandescent and Quartz	2.95m X 4.57m Change House 2.95m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System

Handling Equipment	Safety Equipment
Oil Country 58-93 Tongs c/w Air Back-up Gill Model 300 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment	4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Detector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines

Optional Pump and Tank



RIG #27

OPERATIONS BASE: LLOYDMINSTER

Carrier	BOP Equipment
CBI Drawworks 4210 Engine Cat C-II Rated HP 385 Transmission Allison OFS 4700 Main Drum Brakes 25.4 cm X 106.6 cm Sandline Brakes 20.3 cm X 96.5 cm Drill Line 25.4 mm Sandline 14.28 mm X 2400 m Integrated control panel for X-Celerator	IEL 152 mm Double Gate 35 Mpa Rated Tapped Top 2000 / 5000 Kill Spool C/W 50.8 mm Outlet and Valve 35 Mpa Rated Tapped and Bored for 2000 / 5000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up
Mast	Mobile Doghouse
Courtney Berg 72FS -125,000 21.95 m Height Max Static Hookload 56,000 daN (4 lines) Max Wind Capacity 129 kph Full Setback Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Rod X-Celerator - X-300 Rated 16,000 lbs Blocks 75 Ton McKissick Lighting Incandescent and Quartz	2.85m X 4.57m Change House 2.85m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System
Handling Equipment	Safety Equipment
Oil Country 58-93 Tongs c/w Air Back-up Gill Model 300 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment	4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Detector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines

Optional Pump and Tank



RIG #28

OPERATIONS BASE: LLOYDMINSTER

Carrier	BOP Equipment
CBI Drawworks 4210 Engine Cat C-II Rated HP 385 Transmission Allison OFS 4700 Main Drum Brakes 25.4 cm X 106.6 cm Sandline Brakes 20.3 cm X 96.5 cm Drill Line 25.4 mm Sandline 14.28 mm X 2400 m Integrated control panel for X-Celerator	IEL 152 mm Double Gate 35 Mpa Rated Tapped Top 2000 / 5000 Kill Spool C/W 50.8 mm Outlet and Valve 35 Mpa Rated Tapped and Bored for 2000 / 5000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up

Mast	Mobile Doghouse
Courtney Berg 72FS -125,000 21.95 m Height Max Static Hookload 56,000 daN (4 lines) Max Wind Capacity 129 kph Full Setback Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Rod X-Celerator - X-300 Rated 16,000 lbs Blocks 75 Ton McKissick Lighting Incandescent and Quartz	2.85m X 4.57m Change House 2.85m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System

Handling Equipment	Safety Equipment
Oil Country 58-93 Tongs c/w Air Back-up Gill Model 300 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment	4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Detector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines

Optional Pump and Tank