



RIG #18

OPERATIONS BASE: LLOYDMINSTER

| Carrier  | BOP Equipment   |
|--|---|
| CIL 150<br>Drawworks 4210<br>Engine Cat C-II Rated HP 385<br>Transmission Allison 750<br>Main Drum Brakes 25.4 cm X 106.6 cm<br>Sandline Brakes 20.3 cm X 96.5 cm<br>Drill Line 25.4 mm<br>Sandline 14.28 mm X 3500 m  | Townsend 152 mm Double Gate<br>35 Mpa Rated<br>Tapped Top 2000 / 5000<br>Kill Spool C/W 50.8 mm Outlet and Valve<br>35 Mpa Rated<br>Tapped and Bored for 2000 / 5000<br>73 mm 35 Mpa Tubing Valve<br>Class II Accumulator Control Tech<br>Volume 75 litres Pressure Rating 14 Mpa<br>2 Function Controls c/w Nitrogen Back-up |
| Mast   | Mobile Doghouse   |
| Care Industries 72FS-150,000<br>21.95 m Height<br>Max Static Hookload 66,700 daN (4 lines)<br>Max Wind Capacity 129 kph Full Setback<br>Crown Fall Arrest Rated 5000 lbs<br>Secondary Fall Arrest Rated 5000 lbs<br>Racking Capacity 2100 m 88.9 mm tbg<br>Racking Capacity 2500 m 73 mm tbg<br>Racking Capacity 2800 m 60.3 mm tbg<br>Blocks 75 Ton McKissick<br>Lighting Incandescent and Quartz | 2.95m X 4.57m Change House<br>2.95m X 4.57m Generator House<br>40 kW Isuzu Generator<br>Bathroom Facilities<br>Eagle Link Satellite System  |
| Handling Equipment   | Safety Equipment  |
| Gill 58-93 Tongs c/w Air Back-up<br>Gill Model 300 Rod Tongs<br>Type C Air Slips<br>Standard 60.3 mm & 73 mm tbg Equipment<br>Standard 19mm - 25 mm Rod Equipment  | 4-14 kg Dry Chemical Fire Extinguishers<br>2 Self Contained Breathing Apparatus<br>c/w Spare Cylinder<br>Gas Detector<br>LEL Monitor<br>Safety and Directional Signs<br>Electrical Bonding Equipment<br>Crown Saver<br>Pipe Ram Saver<br>Two Self Retracting Lines  |

Optional Pump and Tank