



RIG #28

OPERATIONS BASE: LLOYDMINSTER

Carrier	BOP Equipment
CBI Drawworks 4210 Engine Cat C-II Rated HP 385 Transmission Allison OFS 4700 Main Drum Brakes 25.4 cm X 106.6 cm Sandline Brakes 20.3 cm X 96.5 cm Drill Line 25.4 mm Sandline 14.28 mm X 2400 m Integrated control panel for X-Celerator	IEL 152 mm Double Gate 35 Mpa Rated Tapped Top 2000 / 5000 Kill Spool C/W 50.8 mm Outlet and Valve 35 Mpa Rated Tapped and Bored for 2000 / 5000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up
Mast	Mobile Doghouse
Courtney Berg 72FS -125,000 21.95 m Height Max Static Hookload 56,000 daN (4 lines) Max Wind Capacity 129 kph Full Setback Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Rod X-Celerator - X-300 Rated 16,000 lbs Blocks 75 Ton McKissick Lighting Incandescent and Quartz	2.85m X 4.57m Change House 2.85m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System
Handling Equipment	Safety Equipment
Oil Country 58-93 Tongs c/w Air Back-up Gill Model 300 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment	4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Detector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines

Optional Pump and Tank