



RIG #9

OPERATIONS BASE: LLOYDMINSTER

Carrier	BOP Equipment
Skytop RR 400 Drawworks 4210 Engine Cat C-10 Rated HP 365 Transmission Allison 750 Main Drum Brakes 25.4 cm X 106.6 cm Sandline Brakes 20.3 cm X 96.5 cm Drill Line 25.4 mm Sandline 14.28 mm X 3500 m Integrated control panel for X-Celerator	Townsend 152 mm Double Gate 35 Mpa Rated Tapped Top 2000 / 5000 Kill Spool C/W 50.8 mm Outlet and Valve 35 Mpa Rated Tapped and Bored for 2000 / 5000 73 mm 35 Mpa Tubing Valve Class II Accumulator Control Tech Volume 75 litres Pressure Rating 14 Mpa 2 Function Controls c/w Nitrogen Back-up
Mast	Mobile Doghouse
Care Industries 72FS-150,000 21.95 m Height Max Static Hookload 66,700 daN (4 lines) Max Wind Capacity 129 kph Full Setback Crown Fall Arrest Rated 5000 lbs Secondary Fall Arrest Rated 5000 lbs Racking Capacity 2100 m 88.9 mm tbg Racking Capacity 2500 m 73 mm tbg Racking Capacity 2800 m 60.3 mm tbg Blocks 75 Ton McKissick Lighting Incandescent and Quartz Integrated X-Celerator unit X-300	2.95m X 4.57m Change House 2.95m X 4.57m Generator House 40 kW Isuzu Generator Bathroom Facilities Eagle Link Satellite System
Handling Equipment	Safety Equipment
Gill 58-93 tongs c/w air back-up Gill Model 300 Rod Tongs Type C Air Slips Standard 60.3 mm & 73 mm tbg Equipment Standard 19mm - 25 mm Rod Equipment	4-14 kg Dry Chemical Fire Extinguishers 2 Self Contained Breathing Apparatus c/w Spare Cylinder Gas Eetector LEL Monitor Safety and Directional Signs Electrical Bonding Equipment Crown Saver Pipe Ram Saver Two Self Retracting Lines

Optional Pump and Tank