



**O'CHIESE EAGLE RIG 1**  
**- INTERNALLY GUYED DOUBLE**  
**Max Depth Capacity: 12,450' Class III**



**MAST**

Mast Type	<i>Telescopic Double</i>	Drill Line Size	1"
Mast MFG	<i>CARE Industries</i>	Number of Lines	6
SHL - Externally Guyed (lb)	<i>200,000</i>	3:1 Capacity (lb)	<i>180,500</i>
SHL - Free Standing (lb)	<i>180,000</i>	2:1 Capacity (lb)	<i>270,700</i>
Mast Clear Height	<i>105'</i>	Sandline Size	<i>1/2" (13,780' Max)</i>
Racking Cap. (3-1/2")	<i>12,450'</i>		

**Hoisting Service Line API Specification for EIPS 6 x 26 is:**

**3 : 1 Safety factor hoisting; 2 : 1 Safety factor pulling on stuck pipe and similar infrequent operations.**

**INTERNAL GUYED COMPONENTS**

Rig Beam MFG	<i>CARE Industries</i>	Geronimo Plate MFG	<i>CARE Industries</i>
Turnbuckles MFG	<i>CARE Industries</i>		

**CARRIER**

Carrier MFG	<i>CARE Industries</i>	Drawworks Drive	<i>CAT C11</i>
Drawworks Model	<i>Hulkster 650-DD</i>	Drive Rating (hp)	<i>385</i>
Rated Power (hp)	<i>450</i>	Transmission	<i>Allison OFS 4700</i>
Main Drum Brake Size	<i>42" x 10"</i>	Sandline Drum Brake Size	<i>38" x 8"</i>
Auxiliary Brake	<i>Kobelt 40" Disc</i>		

**OVERHEAD EQUIPMENT**

Block Type	<i>Oil Country 100T</i>	Block Capacity (ton)	<i>100</i>
Bails Type	<i>King Oil Tools 150T</i>	Bail Capacity (ton)	<i>150</i>
Rod Hook Type	<i>JiangSu RuDong RH-25MK</i>	Rod Hook Capacity (ton)	<i>25</i>
Tbg Elevator Type	<i>Mud King BJ Style</i>	Tbg Elevator Size	<i>2-3/8" to 3-1/2"</i>
Rod Elevator Type	<i>O'Bannon / Mud King</i>	Rod Elevator Size	<i>3/4" to 1"</i>

**HANDLING EQUIPMENT**

Tbg Tongs Type	<i>Oil Country 58-93</i>	Tbg Tongs Size	<i>2-3/8" to 3-1/2"</i>
Air Slips Type	<i>C</i>		

**BOPs (NACE)**

Annular MFG	<i>Boss</i>	Pressure Rating & Size	<i>5,000 psi, 7-1/16"</i>
Double Gate MFG	<i>Boss</i>	Pressure Rating & Size	<i>5,000 psi, 7-1/16"</i>
Kill Spool Pressure Rating & Size			<i>5,000 psi, 7-1/16" c/w 2" Outlet and Valve</i>
Safety Valve Pressure Rating & Size			<i>5,000 psi, 2-7/8" &amp; 3-1/2"</i>
Hydraulic Regan Pressure Rating & Size			<i>3,000 psi, 3" (Type - K)</i>

**ACCUMULATOR**

<b>Class III</b>			
Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (psi)	<i>3,000</i>
Accumulator Vol. (US gal)	<i>40</i>	# of Stations	<i>3</i>



**Sales and Marketing  
Eagle Well Servicing**

**Tel: 1-877-346-9710    Email: sales@eaglerigs.com**

---

**SAFETY EQUIPMENT**

Fire Extinguisher Size (qty)	30 lb (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

**MOBILE DOGHOUSE**

Generator Sets	Yanmar	Prime Rating (hp)	53.6
Change Room Size	15' x 9'-4"	Bathroom Facilities	Yes
Generator House Size	15' x 9'-4"		

**MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)**

Truck MFG & Model	Freightliner 2013	Mud Pump Drive	Detroit DD13
Pump MFG & Model	SJ Petro 300	Pump Drive Rating (hp)	410
Pump Rated Power (hp)	350	Pump Pressure (psi)	5,000
Pump Stroke Length	5"	Centrifugal Pump Size	4" x 3"
Manifold Valve Quantity	7	Transmission	Allison 4500 RDS
Manifold Rating (psi)	5,000	# of Tank Compartments	2
Total Tank Volume (bbl)	200	Line Pipe Rating (psi)	5,000

**MISCELLANEOUS EQUIPMENT (OPTIONAL)**

Rod Tongs Type	M50	Rod Tongs Size	As Required
Rod Backoff Tool Type	Oil Country	Rod Backoff Tool Size	As Required
Low Lying Slips Type	Bosch	Low Lying Slips Size	As Required
Personal H <sub>2</sub> S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head	As Required	Mud Can	As Required
Skid Boiler (hp)	80		

*Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.*

---