

AGLE RIG 22 - INTERNALLY GUYED DOUBLE

Max Depth Capacity: 12,450'

Class III

MAST

M A Western Co.

Mast Type	Telescopic Double	Drill Line Size	1"
Mast MFG	CARE Industries	Number of Lines	6
0111	000 000	0.4.0	400

 SHL - Externally Guyed (lb)
 200,000
 3:1 Capacity (lb)
 180,500

 SHL - Free Standing (lb)
 180,000
 2:1 Capacity (lb)
 270,700

Mast Clear Height 105' Sandline Size 9/16" (13,780' Max)

Racking Cap. (3-1/2") 12,450'

Hoisting Service Line API Specification for EIPS 6 x 26 is:

3: 1 Safety factor hoisting; 2: 1 Safety factor pulling on stuck pipe and similar infrequent operations.

INTERNAL GUYED COMPONENTS

Rig Beam MFG CARE Industries Geronimo Plate MFG CARE Industries

Turnbuckles MFG CARE Industries

CARRIER

Carrier MFG CARE Industries Drawworks Drive CAT C11

Drawworks Model ALCO 42X10 Drive Rating (hp) 385

Rated Power (hp) 450 Transmission Allison OFS 4700

Main Drum Brake Size 42" x 10" Sandline Drum Brake Size 38" x 8"

Auxiliary Brake Kobelt 40" Disc

OVERHEAD EQUIPMENT

Block Type McKissick 100T Block Capacity (ton) 100
Bails Type BVM Tool Pusher 150T Bail Capacity (ton) 150
Rod Hook Type O'Bannon 20T Rod Hook Capacity (ton) 20

Tbg Elevator Type Gearench / Diehl Tbg Elevator Size 2-3/8" to 3-1/2"
Rod Elevator Type O'Bannon Plate Type Rod Elevator Size 3/4" to 1"

HANDLING EQUIPMENT

Tbg Tongs Type Gill 58-93 Tbg Tongs Size 2-3/8" to 3-1/2" Rod Backoff Tool Type BJ Rod Backoff Tool Size 5/8" to 1"

Air Slips Type C

BOPs (NACE)

Annular MFG IEI Pressure Rating & Size 5,000 psi, 7-1/16"

Double Gate MFG IEI Pressure Rating & Size 5,000 psi, 7-1/16"

Kill Spool Pressure Rating & Size 5,000 psi, 7-1/16" c/w 2" Outlet and Valve

Safety Valve Pressure Rating & Size 5,000 psi, 2-7/8" & 3-1/2" Hydraulic Regan Pressure Rating & Size 3,000 psi, 3" (Type - K)

ACCUMULATOR

Class III

Accumulator MFG Control Technology Max Operating Pressure (psi) 3,000
Accumulator Vol. (US gal) 40 # of Stations 3



AGLE Sales and Marketing **Eagle Well Servicing**

Tel: 1-877-346-9710 M A Western Co.

Email: sales@eaglerigs.com

SAFETY EQUIPMENT

Fire Extinguisher Size (qty)	30 lb (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
Tension Limiter	Yes	Pipe Ram Saver	Yes

MOBILE DOGHOUSE

Generator Sets	Isuzu	Prime Rating (hp)	53.6
Change Room Size	15' x 9'-8"	Bathroom Facilities	Yes

Generator House Size 15' x 9'-8"

MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)

Truck MFG & Model	Freightliner 2007	Mud Pump Drive	CAT C11
Pump MFG & Model	SJ Petro 300	Pump Drive Rating (hp)	350
Pump Rated Power (hp)	350	Pump Pressure (psi)	5,000
Pump Stroke Length	5"	Centrifugal Pump Size	4" x 3"

Manifold Valve Quantity 7 Transmission Allison 4500 RDS

2 Manifold Rating (psi) # of Tank Compartments 5,000 Total Tank Volume (bbl) 200 Line Pipe Rating (psi) 5,000

MISCELLANEOUS EQUIPMENT (OPTIONAL)

	•	•	
Rod Tongs Type	M50	Rod Tongs Size	As Required
Low Lying Slips Type	Bosch	Low Lying Slips Size	As Required
Personal H ₂ S Monitor	As Required	NORM Radiation Monitor	As Required
Catwalk	Conventional	Pipe Racks	As Required
Drill Out Head	As Required	Mud Can	As Required
Skid Boiler (hp)	80		

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.