

RIG 26 - INTERNALLY GUYED SINGLE

Max Depth Capacity: 2,800 m

Class II

MAST

Mast Type	<i>Stiff Single</i>	Drill Line Size (mm)	25.4
Mast MFG	<i>CBI</i>	Number of Lines	4
Static Hook Load (daN)	<i>56,000</i>	3:1 Capacity (daN)	55,800
Mast Clear Height (m)	<i>21.9</i>	2:1 Capacity (daN)	83,600
Racking Cap.-88.9mm (m)	<i>2,100</i>	Sandline Size (mm)	14.3 (3,000 m Max)
Racking Cap.-73.0mm (m)	<i>2,500</i>	Racking Cap.-60.3mm (m)	2,800

Hoisting Service Line API Specification for EIPS 6 x 26 is:

3 : 1 Safety factor hoisting; 2 : 1 Safety factor pulling on stuck pipe and similar infrequent operations.

INTERNAL GUYED COMPONENTS

Rig Beam MFG	<i>CBI</i>	Geronimo Plate MFG	<i>CBI</i>
Turnbuckles MFG	<i>CBI</i>		

CARRIER

Carrier MFG	<i>CBI</i>	Drawworks Drive	<i>CAT C11</i>
Drawworks Model	<i>Hulkster 650-DD</i>	Drive Rating (kW)	287
Rated Power (kW)	336	Transmission	<i>Allison OFS 4700</i>
Main Drum Brake Size (mm)	<i>1,067 x 254</i>	Sandline Drum Brake Size (mm)	965 x 203

OVERHEAD EQUIPMENT

Block Type	<i>McKissick 75T</i>	Block Capacity (daN)	66,700
Bails Type	<i>King Oil Tools 130T</i>	Bail Capacity (daN)	115,700
Rod Hook Type	<i>O'Bannon 15T</i>	Rod Hook Capacity (daN)	13,300
Tbg Elevator Type	<i>Diehl / Big "D"</i>	Tbg Elevator Size (mm)	60.3 to 88.9
Rod Elevator Type	<i>O'Bannon/Oil Country/Trico</i>	Rod Elevator Size (mm)	19.1 To 31.8

HANDLING EQUIPMENT

Tbg Tongs Type	<i>Gill 58-93</i>	Tbg Tongs Size (mm)	60.3 to 88.9
Rod Tongs Type	<i>Gill 300</i>	Rod Tongs Size (mm)	19.1 to 25.4
Rod Backoff Tool Type	<i>Oil Country</i>	Rod Backoff Tool Size (mm)	15.9 to 25.5
X-Celerator Type	<i>C-Tech X-300</i>	X-Celerator Capacity (daN)	7,100
Air Slips Type	<i>C</i>		

BOPs (NACE)

Double Gate MFG	<i>IEI</i>	Pressure Rating & Size	34,500 kPa, 179 mm
Kill Spool Pressure Rating & Size			21,000 kPa, 179 mm c/w 50.8 mm Outlet and Valve
Safety Valve Pressure Rating & Size			34,500 kPa, 73.0 mm & 88.9 mm
Hydraulic Regan Pressure Rating & Size			21,000 kPa, 76.2 mm (Type - K)

ACCUMULATOR

Class II			
Accumulator MFG	<i>Control Technology</i>	Max Operating Pressure (kPa)	21,000
Accumulator Vol. (l)	76	# of Stations	2

SAFETY EQUIPMENT

Fire Extinguisher Size (qty)	13.6 kg (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

MOBILE DOGHOUSE

Generator Sets	Yanmar	Prime Rating (kW)	40
Change Room Size (m)	4.57 x 2.95	Bathroom Facilities	Yes
Generator House Size (m)	4.57 x 2.95	Wi-Fi Hotspot Booster	Yes

EQUIPMENT TRUCK WITH PICKER

Crane MFG & Model	Hiab XS MF2010	Crane Lifting Capacity (kg)	4,100
Truck MFG & Model	Freightliner M2		

MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)

Truck MFG & Model	Freightliner 2013	Mud Pump Drive	Detroit DD13
Pump MFG & Model	GD TEE 4 x 5	Pump Drive Rating (kW)	306
Pump Rated Power (kW)	123	Pump Pressure (kPa)	34,500
Pump Stroke Length (mm)	127	Centrifugal Pump Size (mm)	101 x 76
Manifold Valve Quantity	7	Transmission	Allison 4500 RDS
Manifold Rating (kPa)	34,500	# of Tank Compartments	2
Total Tank Volume (m ³)	32	Line Pipe Rating (kPa)	34,500

MISCELLANEOUS EQUIPMENT (OPTIONAL)

Low Lying Slips Type	Bosch	Low Lying Slips Size (mm)	As Required
Personal H ₂ S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head (mm)	As Required	Pipe Trailer	As Required
Skid Boiler (kW)	60	Mud Can	As Required

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.