

## GLE RIG 28 - INTERNALLY GUYED SINGLE

Max Depth Capacity: 9,150'

Class II

#### M A Western Co.

#### **MAST**

Mast Type	Stiff Single	Drill Line Size	1"
Mast MFG	CBI	Number of Lines	4

 Static Hook Load (lb)
 125,000
 3:1 Capacity (lb)
 125,000

 Mast Clear Height
 72'
 2:1 Capacity (lb)
 188,000

Racking Cap. (3-1/2") 12,500' Sandline Size 9/16" (9,840' Max)

Racking Cap. (2-7/8") 8,200' Racking Cap. (2-3/8") 9,150'

Hoisting Service Line API Specification for EIPS 6 x 26 is:

3: 1 Safety factor hoisting; 2: 1 Safety factor pulling on stuck pipe and similar infrequent operations.

#### INTERNAL GUYED COMPONENTS

Rig Beam MFG	CBI	Geronimo Plate MFG	CBI
--------------	-----	--------------------	-----

Turnbuckles MFG CBI

#### **CARRIER**

Carrier MFG	CBI	Drawworks Drive	CAT C11

Drawworks Model Hulkster 650-DD Drive Rating (hp) 385

Rated Power (hp) 450 Transmission Allison OFS 4700

Main Drum Brake Size 42" x 10" Sandline Drum Brake Size 38" x 8"

#### **OVERHEAD EQUIPMENT**

Block Type	McKissick 75T	Block Capacity (ton)	<i>7</i> 5
Bails Type	Cavins 150T	Bail Capacity (ton)	150
Rod Hook Type	Oil Country 35T	Rod Hook Capacity (ton)	35

Tbg Elevator Type Diehl / AOT Tbg Elevator Size 2-3/8" to 3-1/2"
Rod Elevator Type Trico Plate Type Rod Elevator Size 3/4" to 1"

#### HANDLING EQUIPMENT

Tbg Tongs Type Gill 58-93 Tbg Tongs Size 2-3/8" to 3-1/2" Rod Tongs Size 3/4" to 1" Rod Tongs Type Gill 300 Rod Backoff Tool Type Metaltek Machining Rod Backoff Tool Size 3/4" to 1" C-Tech X-300 X-Celerator Capacity (lb) X-Celerator Type 16.000

Air Slips Type C

#### **BOPs (NACE)**

Double Gate MFG HRSB Pressure Rating & Size 3,000 psi, 9"

Kill Spool Pressure Rating & Size 5,000 psi, 9" c/w 2" Outlet and Valve

Safety Valve Pressure Rating & Size 5,000 psi, 2-7/8" & 3-1/2" Hydraulic Regan Pressure Rating & Size 3,000 psi, 3" (Type - K)

#### **ACCUMULATOR**

#### Class II

Accumulator MFG Control Technology Max Operating Pressure (psi) 3,000
Accumulator Vol. (US gal) 20 # of Stations 2



# Sales and Marketing Eagle Well Servicing

Tel: 1-877-346-9710

Email: sales@eaglerigs.com

SAFETY		

M A Western Co.

Fire Extinguisher Size (qty)	30 lb (4)	Gas Detector	Yes
SCBA Quantity	2 w/ Spare Bottle	LEL Monitor	Yes
Self Retracting Lifeline (qty)	2	Crown Saver	Yes
		Pipe Ram Saver	Yes

#### **MOBILE DOGHOUSE**

Generator Sets	Yanmar	Prime Rating (hp)	53.6
Change Room Size	15' x 9'-4"	Bathroom Facilities	Yes
Generator House Size	15' x 9'-4"	Wi-Fi Hotspot Booster	Yes

#### **EQUIPMENT TRUCK WITH PICKER**

Crane MFG & Model	Maxilift ML300.3	Crane Lifting Capacity (lb)	4,510

### Truck MFG & Model Freightliner M2

#### **MOBILE PUMP & TANK (OPTIONAL EQUIPMENT)**

Truck MFG & Model	Freightliner 2002	Mud Pump Drive	Cummins ISC 300
Pump MFG & Model	GD TEE 4 x 5	Pump Drive Rating (hp)	300
Pump Rated Power (hp)	165	Pump Pressure (psi)	3,000
Pump Stroke Length	5"	Bowie Pump Size	3"
Manifold Valve Quantity	7	Transmission	Allison MD3560
Manifold Rating (psi)	3,000	# of Tank Compartments	2
Total Tank Volume (bbl)	189	Line Pipe Rating (psi)	5,000

#### MISCELLANEOUS EQUIPMENT (OPTIONAL)

Low Lying Slips Type	Bosch	Low Lying Slips Size	As Required
Personal H <sub>2</sub> S Monitor	As Required	NORM Radiation Monitor	As Required
Drill Out Head	As Required	Pipe Trailer	As Required
Skid Boiler (hp)	80	Mud Can	As Required

Standard specifications represent the typical rig configuration, but could be subject to slight modifications from time to time due to customer requirements.